



# Product Information: **MAGNOL STOU 15W-30** **UNIVERSAL FARM OIL**

## **Description**

Magnol STOU 15W-30 is a universal product suitable for use in a wide variety of older agricultural machines.

It can be used in four stroke, naturally aspirated and turbo-charged diesel engines and four stroke petrol engines fitted on farm machinery, where it provides good standards of engine cleanliness and protection for components.

The product performs well in hydraulic systems, where it protects pumps, system components and rams against wear and corrosion. It is formulated to release entrained air and help prevent sponginess in system operation.

Magnol STOU 15W-30 can also be used in hydrostatic transmissions on tractors, combine harvesters, where a universal type product is recommended by the manufacturer and where oil immersed or wet brakes may be fitted.

## **Applications**

Magnol STOU 15W-30 can be used where any of the performance levels listed below are specified by the equipment manufacturer.

## **Performance Levels**

- API CF-4/SF
- Massey Ferguson M1139
- Ford M2C 159B
- API GL-4
- Caterpillar TO-2
- Allison C4

## **Physical Characteristics**

Appearance	Amber Liquid
Relative Density at 15°C	0.886
Kinematic Viscosity @ 40°C (cSt)	81.54
Kinematic Viscosity @ 100°C (cSt)	11.53
Viscosity Index	133
CCS @ -20 (mPa.s)	7000 max
Closed Flash Point (°C)	163
Pour Point (°C)	-30
TBN (mgKOH/g)	11.50

Figures based on average production values

(TDS Magnol STOU 15W-30 – 080316 Issue 11)

