



Product Information:

## **SERVOL PERFORMANCE PLUS 15W-40 AUTOMOTIVE ENGINE OIL**

### **Description**

Servol Performance Plus 15W-40 is manufactured from high quality mineral oils and a high performance additive system. This grade is designed for use in petrol and diesel engines and their turbocharged versions.

Servol Performance Plus 15W-40 provides a good level of engine cleanliness and controls the formation of high temperature lacquers and low temperature sludges. Anti-wear technology ensures maximum component life, together with protection from oxidation, rust and corrosion.

### **Applications**

Typical applications for Servol Performance Plus 15W-40 include pre-2004 passenger cars and vans and commercial vehicles (Euro 1 and Euro 2 compliant), where the following would have been originally stated: MB 228.1, MAN 271, Mack EO-L, Volvo VDS and VW 505.00.

Note: This product must never be used in engines incorporating after-treatment devices. This includes: exhaust gas re-circulation (EGR), diesel particulate filters (DPFs) and adblue systems.

### **Performance Levels**

API CG-4 / CF-4 / SJ / SL

### **Physical Characteristics**

Density at 15.6 °C	0.880
Viscosity @ 100 °C, cSt.	14.4
Viscosity @ 40 °C, cSt.	102.0
Viscosity Index	143
Flash Point (Closed) °C	201
TBN, mg/KOH/g	9.7
Pour Point, °C	-36

Figures based on average production values.

Part No.s: SPP001, SPP005, SPP025, SPP205

(TDS Servol Performance Plus 15W-40 - 291015 Issue 16)

