



Product Information:

MLR RACING BRAKE FLUID COMPETITION AND MOTORSPORT

Description

MLR Racing Brake Fluid has been specially formulated to maximise performance under the extreme temperature conditions experienced in motorsport. The fluid maintains its integrity under the most arduous of operating scenarios ensuring positive and effective braking.

MLR Racing Brake Fluid is blended with special additives that prevent fluid oxidation, rust and the swelling of the piston seals used in conventional brake systems and is compatible with all other non-mineral brake fluids manufactured to the same specifications.

Applications:

MLR Racing Brake Fluid is suitable for use in all brake and clutch systems, where a non-mineral oil grade has been specified meeting the performance levels listed below.

Always check manufacturer's handbooks for the correct fluid type as mis-application will impair brake operation and pose a threat to vehicle safety.

Performance Levels:

U.S. Federal Motor Vehicle Safety Standard
U.S. Society of Automotive Engineers

FMVSS 116 DOT 4
SAE J 1703 and J 1704

Physical Characteristics:

Appearance	Water white to amber
Density @ 20°C	1.078
pH value	7.0 – 11.5
Viscosity @ -40°C (cSt)	1800 max
ERBP (°C)	320 min
Wet ERBP (°C)	195 min

Part No.s: TBA

(TDS MLR Racing Brake Fluid – 310516 Issue 1)

