



Product Information:

MULTITRANS TMX 75W-90 **FULLY SYNTHETIC GEAR LUBRICANT**

Description

Multitrans TMX 75W-90 is a synthetic high performance gear oil that has excellent extreme pressure (EP) performance and load carrying ability, as well as providing rust and corrosion protection to transmission components.

This grade not only has outstanding low temperature fluidity, eliminating cold start gear selection problems (cold baulking), but can also cope with highly stressed gearboxes running at high temperatures. The extremely strong synthetic base fluid maintains lubricating film integrity under the toughest shock load conditions demonstrating superior performance over conventional mineral oils.

Multitrans TMX 75W-90 offers the following benefits:

- Improved gear-shift
- Outstanding low temperature fluidity
- Enhanced thermal and oxidation stability
- Foam control
- Contributes to overall fuel efficiency

Applications

Multitrans TMX 75W-90 gear oil is designed and recommended for use where manufacturers specify any of the performance levels listed below.

Performance Level

API GL4
MB 235.11
MAN 341 Type MB
ZF TE-ML 08

Physical Characteristics

Density at 15°C	0.849
Viscosity at 100°C, cSt.	14.5
Viscosity at 40°C, cSt.	96.5
Viscosity Index	158
Flash Point (Closed) °C	223
Pour Point, °C	-51

Figures based on average production values.

(TDS Multitrans TMX 75W-90 – 080216 Issue 1)

