



Product Information:
LIQUIMATIC DX14
SPECIALISED TRANSMISSION FLUID

Description

Liquimatic DX14 is an advanced automatic transmission fluid, primarily developed for use in Mercedes Benz 7-speed RWD (Rear Wheel Drive) automatic gearboxes and all AMG models. The product ensures efficient and effective gearshift under a variety of loads and operating conditions.

Applications

Recommended for the latest generation of MB 7-speed RWD automatic gearboxes (NAG 2). This product is the only acceptable transmission fluid for NAG2V Sport transmissions and the 7G-Tronic models: W7A 700 / NAG2. Additional applications include 5-speed models that employ a controlled torque converter lockup clutch for rear-wheel drive vehicles, which are also fitted in certain Chrysler models. These model designations are: 722.6 / W5A 580 / NAG1.

Note: Not for use in 722.9, NAG2FE applications or where MB236.15 is specified.

Benefits

- Ensures positive and continuous frictional control
- Smooth vibration free operation
- High level of thermal and oxidative stability
- Excellent shear stability characteristics that maintain system pressure
- Reduced fluid loss through due to low volatility

Performance Levels

MB-Approval 236.14. Meets the requirements of MB 236.1/6/7/9/10/12

Proven performance in the latest 6HP & 8HP speed where the following has been specified:

BMW Part No. 8322 2152426

Chrysler Part No. 68157995AA

Jaguar Part No. 02JDE 26444

Land Rover Part No. LR023288

VW Part No. G 055 005 A1/A2/A6, VW Part No. G 060 162 A2, VW TL 52533 (G 052 533)

Lifeguard Fluid 8 - 6HP19X - for Audi Q7

Physical Characteristics

Appearance	Red
Viscosity @ 100°C, cSt.	6.4
Viscosity @ 40°C, cSt.	29.7
Density at 15.6°C	0.848
Flash Point (Open) °C	180 min.

Note: Demonstrated 'no harm in use' in applications where ATF 3403 is required.

Part No.s: MBF001, MBF005, MBF025, MBF205

(TDS Liquimatic DX14 – 030516 Issue 5)

