



Product Information:

MULTIVIS ECO C2 0W-30

SYNTHETIC TECHNOLOGY – FUEL EFFICIENT

(Previously known as – Multilife C-TWO 0W-30)

Description

Multivis ECO C2 0W-30 is a mid-SAPS (Sulphur, Ash, Phosphorus) synthetic technology based engine oil specially formulated to meet the superior performance and fuel efficiency requirements of engines requiring low viscosity oils for gasoline and diesel engine applications.

Multivis ECO C2 0W-30 has been developed for use in Euro IV, V and VI compliant vehicles with DPF after treatment devices.

Multivis ECO C2 0W-30 provides:

1. Increased engine efficiency, output and improved fuel economics.
2. Excellent cold starting characteristics, reducing noise and wear.
3. Improved flow rates to bearings at low temperatures and increased film strength at high temperatures.
4. Better high temperature operation and anti-sludge control.
5. Low levels of volatility.
6. Better thermal stability, improved engine cleanliness.
7. Mid-SAPS (Sulphur, Ash, Phosphorus) product, for improved DPF (Diesel Particulate Filter) performance.

Applications

Recommended for petrol and diesel engines, requiring a low viscosity ACEA C2 0W-30 oil, e.g. Honda, or where any of the specifications listed below are required.

Performance Levels

ACEA C2

ACEA C3

BMW Longlife-04

Physical Characteristics

Viscosity @ 100°C, cSt.	9.62
Viscosity @ 40°C, cSt.	51.04
Viscosity Index	177
Density @ 15.6°C	0.840
Flash Point (Closed) °C	201
TBN, mg/KOH/g	7.03
Pour Point, °C	-48

Figures based on average production values.

Part No.s: WFT001, WFT005, WFT025, WFT205

(TDS Multivis ECO C2 0W-30 – 120716 Issue 1)

