



Product Information:  
**MULTITRANS MPC**  
**VERSATILE TRANSMSSION FLUID**

**Description**

Multitrans MPC is a high performance, fully synthetic transmission fluid, designed to provide rationalization opportunities without compromising performance.

Multitrans MPC provides high levels of component protection over a wide range of operating temperatures and workloads. The product will deliver the correct levels of friction control in a wide range of transmission units, ensuring positive gear shift and maximising power output

**Features**

- Extended drain interval capability due to excellent oxidation stability
- Outstanding low temperature fluidity
- Superior oxidation and thermal stability control
- Advanced wear control
- Improved friction retention

**Applications**

The product may also be used in passenger car transmissions, power steering systems, or in certain hydraulic applications, where a fluid of this type and specification is required.

**Note:** Must not be used in Continuously Variable Transmission, Double Clutch Transmissions or applications requiring a Ford Type F / G fluid

**Performance Levels**

General Motors DEXRON® IID, IIIG, IIIG Ford MERCON® V, FNR5 Ford ESP-M2C-138-CJ / 166-H Mopar AS68RC Chrysler ATF +3, ATF +4 Honda ATF Z-1 Hyundai/Kia SP-II, SP-III, JWS 3314 /3317 Kia Red-1 Idemitsu K17 (JATCO) JASO 1A JWS 3309 (Aisin Warner) Mazda ATF-M III, ATF-MV Mitsubishi Diaqueen ATF J2,J3, SP-II, SP-III, PA Nissan 402, Nissan Matic-D, J, K Subaru ATF, ATF-HP Suzuki 3314, 3317 Toyota T, T-II, T-III, T-IV (JWS 3309)	Audi G 052 162, G 052 990, G 055 025 VW TL 52162 – (Factory fill product – Yellow) BMW LA 2634, LT 71141 ETL-7045E (BMW 3 Series) ETL-8072B (BMW 5 Series) Mercedes Benz MB 236.1/2/3/5/6/7/9/11/81 Mercedes Benz MB 236.10 (NAG-1 / Shell 3403) PSA AL-4 Renault DP-0 Texaco N402 (JATCO) Volvo 4-6 Speed ZF TE-ML 09, 11A/11B ZF TE-ML 03D, 09, 11B, 14A, 14B, 16L, 17C Saab 3309  <i>Also suitable for use in applications requiring MB 236.12/14</i>
---	---

**Physical Characteristics**

Appearance	Red
Density @ 15.6°C	0.855
Viscosity @ 100°C, cSt.	7.10
Viscosity @ 40°C, cSt.	34.71
Viscosity Index	187
Flash Point (Closed) °C	170
Pour Point, °C	-48

Figures based on average production values.

Part No.s : MPC001, MPC005, MPC025, MPC205

(TDS Multitrans MPC - 310117 Issue 9)

